

CELESTIAL LED

The Celestial provides a high quality lighting solution, where 15mm and 24mm exposed T-bar ceilings are used. It utilises back mounted LEDs for superior light distribution.

FEATURES

- Luminaire suitable for 15mm and 24mm exposed T grid system
- The LEDs are back mounted within the luminaire for superior light distribution
- Manufactured from mild steel



TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cw
CE-20-55-4K-HE	20W 495 x 495 LED Luminaire	2 x 36W PL	4.2	50	5A 37µs	20	3469	2497	124.9
CE-20-4K-HE	20W 595 x 595 LED Luminaire	4 x 14WT5	4.8	50	5A 37µs	20	3469	2497	124.9
CE-27-4K-HE	27W 595x 595 LED Luminaire	4 x 24WT5	4.8	50	5A 37µs	27	4683	3371	124.9
CE-20-123-4K-HE	20W 1195 x 295LED Luminaire	2 x 28WT5	4.8	50	5A 37µs	20	3469	2497	124.9
CE-27-123-4K-HE	27W 1195 x 295 LED Luminaire	2 x 28WT5	4.8	50	5A 37µs	27	4683	3371	124.9
CE-54-126-4K-HE	54W 1195 x 595 LED Luminaire	4 x 54WT5	8.5	20	12A 50µs	54	9365	6743	124.9

OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
- EMST** Integral Emergency Self Test (1W)
- CF** Corridor Function
- MWP** Remote Programmable Microwave
- WL** Wireless Control System
- WLEM** Wireless Emergency Monitoring
- DD** SwitchDIM/DALI
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

