

FUSION LED

The Fusion is a stylish luminaire designed to have a modern flair, without compromise.

FEATURES

- Luminaire suitable for 15mm and 24mm exposed T grid system
- Manufactured from mild steel
- Constant output driver
- IP40 Rated



LED

IP40

T5
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cw
FUS-20-55-4K-HE	20W 495 x 495 LED Luminaire	2 x 36W PL	4.2	50	5A 37µs	20	3469	2497	124.9
FUS-20-4K-HE	20W 595 x 595 LED Luminaire	4 x 14W T5	4.8	50	5A 37µs	20	3469	2497	124.9
FUS-27-4K-HE	27W 595 x 595 LED Luminaire	4 x 24W T5	4.8	50	5A 37µs	27	4683	3371	124.9
FUS-20-123-4K-HE	20W 1195 x 295 LED Luminaire	2 x 28W T5	4.8	50	5A 37µs	20	3469	2497	124.9
FUS-27-123-4K-HE	27W 1195 x 295 LED Luminaire	2 x 28W T5	4.8	50	5A 37µs	27	4683	3371	124.9
FUS-54-126-4K-HE	54W 1195 x 595 LED Luminaire	4 x 54W T5	8.5	20	12A 50µs	54	9365	6743	124.9

OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
- EMST** Integral Emergency Self Test (1W)
- CF** Corridor Function
- MWP** Remote Programmable Microwave
- WL** Wireless Control System
- WLEM** Wireless Emergency Monitoring
- DD** SwitchDIM/DALI
- TPA** TPA Option
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

