

KNIGHT ROUND LED

This range of robust outdoor amenity products are IP65 surface mounted luminaires constructed of die-cast aluminium housing with UV stabilised polycarbonate vandal resistant diffuser.

FEATURES

- IK10 Rated
- IP65 die-cast aluminium construction
- Allen key entry
- 5 Year warranty



IK10

IP65

2D
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cw
KNIR 10-CO-4K	10W LED Amenity Luminaire	16W 2D	2.2	65	8A 80µs	10	1734	1040	104.0
KNIR 14-CO-4K	14W LED Amenity Luminaire	28W 2D	2.2	45	10A 100µs	14	2428	1460	104.0
KNIR 21-CO-4K	21W LED Amenity Luminaire	38W 2D	2.2	45	10A 100µs	21	3642	2185	104.0

OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
EMST Integral Emergency Self Test (1W)
WL Wireless Control System
WLEM Wireless Emergency Monitoring
DD SwitchDIM/DALI
3K 3000K Colour Temperature
5K 5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

